45-1

Customer product reference: Z10504

Hot-line clamp

For overhead primary tap connections, with a copper-alloy body, tinned finish and lock washers at the main and tap connections.



Representative manufacturer image. Confirm markings, configuration and installation requirements with Zeus.

Construction & ratings

Rated current	400 A
Rated voltage	Up to and including 36 kV
Frequency	50/60 Hz
Body	Copper alloy
Finish	Tinned

Dimensions & packaging

Length	3.15 in
Width	2.19 in
Height	6.28 in
Mass	0.744 lb
Standard pack	50

Manufacturer environmental data

Maximum relative humidity	95%
Maximum operating conductor temperature	93°C (200°F)
Maximum operating altitude	4000 m (13123 ft)

Additional manufacturer details

Keeper	Aluminum bronze
Eye stem	Aluminum bronze
Eye bolt	Aluminum bronze
Lock washers	Bronze alloy
Manufacturer packaging	Wooden box (manufacturer states ISPM 15 compliant)

Confirm before ordering

Manufacturer product data. Confirm the exact conductor combination, application and current installation documentation with Zeus before ordering.

Selection and quotation summary. Obtain the applicable manufacturer installation instructions and approved conductor combination before use.

Source: supplied Incesa document 3031430034-EN / REV. 0 /2025; p. 1, Features, General, Dimensions and Logistics. Manufacturer data summarized by Zeus.